

AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : AXIAL 50 EC

Design code : A13617AV

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Herbicide

1.3 Details of the supplier of the safety data sheet

Company : Syngenta Crop Protection AG
Postfach
CH-4002 Basel
Switzerland

Telephone : +41 61 323 11 11

Telefax : +41 61 323 12 12

E-mail address of person responsible for the SDS : sds.ch@syngenta.com

1.4 Emergency telephone number

Emergency telephone number : +44 1484 538444

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (**REGULATION (EC) No 1272/2008**)

Acute toxicity, Category 4

H332: Harmful if inhaled.

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

Chronic aquatic toxicity, Category 2



H411: Toxic to aquatic life with long lasting effects.

AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	 
Signal word	:	Warning
Hazard statements	:	H317 May cause an allergic skin reaction. H332 Harmful if inhaled. H411 Toxic to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH401 To avoid risks to human health and the environment, comply with the instructions for use. EUH208 Contains cloquintocet-mexyl. May produce an allergic reaction. EUH208 Contains pinoxaden. May produce an allergic reaction.
Precautionary statements	:	Prevention: P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P280 Wear protective gloves. Response: P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

pinoxaden
cloquintocet-mexyl

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL 50 EC

Version
11.0

Revision Date:
21.11.2017

SDS Number:
S1450086294

This version replaces all previous versions.

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
solvent naphtha (petroleum), heavy arom.	64742-94-5 265-198-5 649-424-00-3 01-2119451151-53	Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 25 - < 30
2-methylpentane-2,4-diol	107-41-5 203-489-0 603-053-00-3 01-2119539582-35	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 10 - < 20
pinoxaden	243973-20-8	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1A; H317 STOT SE 3; H335 Aquatic Chronic 3; H412	>= 2.5 - < 10
cloquintocet-mexyl	99607-70-2 01-2119381871-32	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2.5
naphthalene	91-20-3 202-049-5 601-052-00-2	Flam. Sol. 2; H228 Acute Tox. 4; H302 Carc. 2; H351 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.25 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Have the product container, label or Safety Data Sheet with you when calling the emergency number, a poison control center or physician, or going for treatment.

If inhaled : Move the victim to fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Keep patient warm and at rest.
Call a physician or poison control centre immediately.

AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with plenty of water.
If skin irritation persists, call a physician.
Wash contaminated clothing before re-use.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,
for at least 15 minutes.
Remove contact lenses.
Immediate medical attention is required.
- If swallowed : If swallowed, seek medical advice immediately and show this
container or label.
Do not induce vomiting: contains petroleum distillates and/or
aromatic solvents.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : There is no specific antidote available.
Treat symptomatically.
Do not induce vomiting: contains petroleum distillates and/or
aromatic solvents.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Extinguishing media - small fires
Use water spray, alcohol-resistant foam, dry chemical or
carbon dioxide.
Extinguishing media - large fires
Alcohol-resistant foam
or
Water spray
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread
fire.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : As the product contains combustible organic components, fire
will produce dense black smoke containing hazardous
products of combustion (see section 10).
Exposure to decomposition products may be a hazard to
health.

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear full protective clothing and self-contained breathing
apparatus.
- Further information : Do not allow run-off from fire fighting to enter drains or water

AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

courses.
Cool closed containers exposed to fire with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Clean contaminated surface thoroughly.
Clean with detergents. Avoid solvents.
Retain and dispose of contaminated wash water.

6.4 Reference to other sections

For disposal considerations see section 13., Refer to protective measures listed in sections 7 and 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : No special protective measures against fire required.
Avoid contact with skin and eyes.
When using do not eat, drink or smoke.
For personal protection see section 8.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No special storage conditions required. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs.

Further information on storage stability : Physically and chemically stable for at least 2 years when stored in the original unopened sales container at ambient temperatures.

7.3 Specific end use(s)

Specific use(s) : For proper and safe use of this product, please refer to the approval conditions laid down on the product label.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL 50 EC

Version
11.0

Revision Date:
21.11.2017

SDS Number:
S1450086294

This version replaces all previous versions.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
solvent naphtha (petroleum), heavy arom.	64742-94-5	TWA	8 ppm 50 mg/m ³	Supplier
2-methylpentane-2,4-diol	107-41-5	STEL	20 ppm 98 mg/m ³	CH SUVA
	107-41-5	TWA	10 ppm 49 mg/m ³	CH SUVA
pinoxaden	243973-20-8	TLV-C	0.1 mg/m ³	Syngenta
cloquintocet-mexyl	99607-70-2	TWA	5 mg/m ³	Syngenta
naphthalene	91-20-3	TWA	10 ppm 50 mg/m ³	91/322/EEC
Further information	Indicative			
	91-20-3	TWA	10 ppm 50 mg/m ³	CH SUVA
Further information	Toxic by skin resorption possible; Substances, which are easily absorbed through the skin, can give by additional skin resorption a substantial higher risk compared to only inhalation by the airways., Carcinogenic Category 3, National Institute for Occupational Safety and Health, Occupational Safety and Health Administration			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
tris(2-ethylhexyl) phosphate	Workers	Inhalation	Long-term systemic effects	350 mg/m ³
	Workers	Inhalation	Acute systemic effects	2800 mg/m ³
	Workers	Dermal	Long-term systemic effects	50 mg/kg
	Workers	Dermal	Acute systemic effects	40 mg/kg
	Consumers	Dermal	Acute systemic effects	200 mg/kg
	Consumers	Dermal	Long-term systemic effects	25 mg/kg
	Consumers	Inhalation	Acute systemic effects	500 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	62.5 mg/m ³
	Consumers	Oral	Acute systemic effects	200 mg/kg
	Consumers	Oral	Long-term systemic effects	25 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL 50 EC

Version
11.0

Revision Date:
21.11.2017

SDS Number:
S1450086294

This version replaces all previous versions.

Substance name	End Use	Exposure routes	Potential health effects	Value
2-methylpentane-2,4-diol	Workers	Inhalation	Short-term exposure, Local effects	98 mg/m ³
	Workers	Inhalation	Long-term systemic effects	14 mg/m ³
	Workers	Inhalation	Long-term local effects	49 mg/m ³
	Workers	Dermal	Long-term systemic effects	2 mg/kg
	Consumers	Inhalation	Short-term exposure, Local effects	49 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	3.5 mg/m ³
	Consumers	Inhalation	Long-term local effects	25 mg/m ³
	Consumers	Oral	Long-term systemic effects	1 mg/kg
	Consumers	Dermal	Long-term systemic effects	1 mg/kg
	cloquintocet-mexyl	Industrial use	Dermal	Long-term exposure, Systemic effects
Industrial use		Inhalation	Long-term exposure, Systemic effects	0.303 mg/m ³
solvent naphtha (petroleum), heavy arom.	Industrial use	Dermal	Long-term systemic effects	12.5 mg/kg
	Industrial use	Inhalation	Long-term systemic effects	151 mg/m ³
	Consumers	Dermal	Long-term systemic effects	7.5 mg/kg
	Consumers	Oral	Long-term systemic effects	32 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	7.5 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
tris(2-ethylhexyl) phosphate	Sewage treatment plant	1 mg/l
	Fresh water	0.429 mg/l
	Marine water	0.0429 mg/l
	Fresh water sediment	1.79 mg/kg
	Marine sediment	0.179 mg/kg
	Soil	0.11 mg/kg
cloquintocet-mexyl	Fresh water	0.0018 mg/l
	Fresh water sediment	0.934 mg/kg dry weight (d.w.)
	Marine water	0.00018 mg/l
	Marine sediment	0.0934 mg/kg dry weight (d.w.)
	Soil	0.463 mg/kg dry

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

Substance name	Environmental Compartment	Value
		weight (d.w.)

8.2 Exposure controls

Engineering measures

Containment and/or segregation is the most reliable technical protection measure if exposure cannot be eliminated.

The extent of these protection measures depends on the actual risks in use.

Maintain air concentrations below occupational exposure standards.
Where necessary, seek additional occupational hygiene advice.

Personal protective equipment

Eye protection : No special protective equipment required.

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : 0.5 mm

Remarks : Wear protective gloves. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Remove and wash contaminated clothing before re-use.
Wear as appropriate:
Impervious clothing

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Suitable respiratory equipment:
Respirator with a particle filter (EN 143)
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

- Filter type : Particulates type (P)
- Protective measures : The use of technical measures should always have priority over the use of personal protective equipment. When selecting personal protective equipment, seek appropriate professional advice.
-

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

: liquid, clear

Colour : light yellow to orange brown

Odour : sweetish

Odour Threshold : No data available

pH : 4.5
Concentration: 1 % w/v

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : 103 °C(1025.0 hPa)
Method: Pensky-Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure :
No data available

Relative vapour density : No data available

Density : 0.965 g/cm³ (25 °C)

Solubility(ies)
Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

Auto-ignition temperature : 380 °C

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : 50 mPa.s (20 °C)
22.39 mPa.s (40 °C)

Viscosity, kinematic : 24.23 mm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Surface tension : 30.0 mN/m, 20 °C

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Ingestion
Inhalation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL 50 EC

Version
11.0

Revision Date:
21.11.2017

SDS Number:
S1450086294

This version replaces all previous versions.

Skin contact
Eye contact

Acute toxicity

Product:

Acute oral toxicity

: LD50 (Rat, female): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity

: LC50 (Rat, male and female): > 2.42 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.

Acute dermal toxicity

: LD50 (Rat, male and female): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Components:

2-methylpentane-2,4-diol:

Acute oral toxicity

: LD50 Oral (Rat): 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity

: LC50 (Rat): 70 ppm
Exposure time: 8 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity

: LD50 Dermal (Rat): 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

pinoxaden:

Acute oral toxicity

: LD50 (Rat, male and female): > 5,000 mg/kg

Acute inhalation toxicity

: LC50 (Rat, male): 4.63 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity

: LD50 (Rat, male and female): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

cloquintocet-mexyl:

Acute oral toxicity

: LD50 (Rat, male and female): > 5,000 mg/kg

Acute inhalation toxicity

: LC50 (Rat, male and female): > 0.935 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Highest attainable concentration

Acute dermal toxicity

: LD50 (Rat, male and female): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

naphthalene:

Acute oral toxicity

: Assessment: The component/mixture is moderately toxic after single ingestion.

Skin corrosion/irritation

Product:

Species: Rabbit
Result: Mild skin irritation

Components:

2-methylpentane-2,4-diol:

Species: Rabbit
Result: Irritating to skin.

pinoxaden:

Method: Based on Human Evidence
Result: Irritating to skin.

cloquintocet-mexyl:

Species: Rabbit
Result: No skin irritation

Serious eye damage/eye irritation

Product:

Species: Rabbit
Result: No eye irritation

Components:

2-methylpentane-2,4-diol:

Species: Rabbit
Result: Irritation to eyes, reversing within 21 days

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL 50 EC

Version
11.0

Revision Date:
21.11.2017

SDS Number:
S1450086294

This version replaces all previous versions.

pinoxaden:

Species: Rabbit

Result: Irritation to eyes, reversing within 21 days

cloquintocet-mexyl:

Species: Rabbit

Result: No eye irritation

Respiratory or skin sensitisation

Product:

Test Type: Buehler Test

Species: Guinea pig

Result: May cause sensitisation by skin contact.

Components:

pinoxaden:

Test Type: mouse lymphoma cells

Species: Mouse

Result: The product is a skin sensitiser, sub-category 1A.

Test Type: Respiratory sensitisation

Result: Does not cause respiratory sensitisation.

Remarks: Experience with human exposure

cloquintocet-mexyl:

Species: Guinea pig

Result: May cause sensitisation by skin contact.

Germ cell mutagenicity

Components:

2-methylpentane-2,4-diol:

Germ cell mutagenicity-Assessment : In vitro tests did not show mutagenic effects

pinoxaden:

Germ cell mutagenicity-Assessment : Animal testing did not show any mutagenic effects.

cloquintocet-mexyl:

Germ cell mutagenicity-Assessment : Animal testing did not show any mutagenic effects.

Carcinogenicity

Components:

2-methylpentane-2,4-diol:

AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

pinoxaden:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

cloquintocet-mexyl:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

naphthalene:

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Components:

2-methylpentane-2,4-diol:

Reproductive toxicity - Assessment : No toxicity to reproduction

pinoxaden:

Reproductive toxicity - Assessment : No toxicity to reproduction

cloquintocet-mexyl:

Reproductive toxicity - Assessment : No toxicity to reproduction

STOT - single exposure

Components:

pinoxaden:

Assessment: Based on Human Evidence, The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

Remarks: Breathing difficulties

Cough

Acute irritation of the respiratory system leading to tightness of the chest and an asthmatic condition.

cloquintocet-mexyl:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

STOT - repeated exposure

Components:

pinoxaden:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

cloquintocet-mexyl:

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Repeated dose toxicity

Components:

cloquintocet-mexyl:

Remarks: No adverse effect has been observed in chronic toxicity tests.

Aspiration toxicity

Components:

solvent naphtha (petroleum), heavy arom.:

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Product:

- | | | |
|---|---|---|
| Toxicity to fish | : | LC50 (Danio rerio (zebra fish)): 70.71 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 1.8 mg/l
Exposure time: 48 h |
| Toxicity to algae | : | ErC50 (Pseudokirchneriella subcapitata (green algae)): 61 mg/l
Exposure time: 72 h |

NOEC (Pseudokirchneriella subcapitata (green algae)): 6.4 mg/l
End point: Growth rate
Exposure time: 72 h

Components:

solvent naphtha (petroleum), heavy arom.:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

pinoxaden:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 10.3 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL 50 EC

Version
11.0

Revision Date:
21.11.2017

SDS Number:
S1450086294

This version replaces all previous versions.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 52 mg/l
Exposure time: 48 h

LC50 (Americamysis bahia (Mysid shrimp)): 4.7 mg/l
Exposure time: 96 h

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 41 mg/l
Exposure time: 72 h

ErC50 (Skeletonema costatum (marine diatom)): 1.72 mg/l
Exposure time: 72 h

NOEC (Skeletonema costatum (marine diatom)): 0.94 mg/l
End point: Growth rate
Exposure time: 96 h

NOEC (Lemna gibba (gibbous duckweed)): 0.73 mg/l
End point: Growth rate
Exposure time: 7 d

Toxicity to fish (Chronic toxicity) : NOEC: 6.6 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)

cloquintocet-mexyl:

Toxicity to fish

: LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.97 mg/l
Exposure time: 96 h

LC50 (Gobiocypris rarus (rare gudgeon)): 0.102 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0.82 mg/l
Exposure time: 48 h

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): > 2.2 mg/l
Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 0.12 mg/l
End point: Growth rate
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 0.437 mg/l
Exposure time: 21 d
Species: Daphnia (water flea)

naphthalene:

AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.
Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

2-methylpentane-2,4-diol:

Biodegradability : Result: Readily biodegradable.

pinoxaden:

Biodegradability : Result: rapidly degradable
Stability in water : Degradation half life: 0.3 d
Remarks: Product is not persistent.

cloquintocet-mexyl:

Biodegradability : Result: Not readily biodegradable.
Stability in water : Degradation half life: 0.4 d
Remarks: Product is not persistent.

12.3 Bioaccumulative potential

Components:

pinoxaden:

Bioaccumulation : Remarks: Low bioaccumulation potential.
Partition coefficient: n-octanol/water : log Pow: 3.2 (25 °C)

cloquintocet-mexyl:

Bioaccumulation : Remarks: Does not bioaccumulate.
Partition coefficient: n-octanol/water : log Pow: 5.24 (25 °C)

12.4 Mobility in soil

Components:

pinoxaden:

Distribution among environmental compartments : Remarks: Moderately mobile in soils

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

Stability in soil : Dissipation time: 0.1 - 1.8 d
Percentage dissipation: 50 % (DT50)
Remarks: Product is not persistent.

cloquintocet-mexyl:

Distribution among environmental compartments : Remarks: immobile

Stability in soil : Dissipation time: 2.4 d
Percentage dissipation: 50 % (DT50)
Remarks: Product is not persistent.

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

2-methylpentane-2,4-diol:

Assessment

: This substance is not considered to be persistent, bioaccumulating and toxic (PBT).. This substance is not considered to be very persistent and very bioaccumulating (vPvB)..

pinoxaden:

Assessment

: This substance is not considered to be persistent, bioaccumulating and toxic (PBT).. This substance is not considered to be very persistent and very bioaccumulating (vPvB)..

cloquintocet-mexyl:

Assessment

: This substance is not considered to be persistent, bioaccumulating and toxic (PBT).. This substance is not considered to be very persistent and very bioaccumulating (vPvB)..

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not contaminate ponds, waterways or ditches with

AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

chemical or used container.
Do not dispose of waste into sewer.
Where possible recycling is preferred to disposal or incineration.
If recycling is not practicable, dispose of in compliance with local regulations.

Contaminated packaging : Empty remaining contents.
Triple rinse containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number

ADN : UN 3082
ADR : UN 3082
RID : UN 3082
IMDG : UN 3082
IATA : UN 3082

14.2 UN proper shipping name

ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(SOLVENT NAPHTHA)
ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(SOLVENT NAPHTHA)
RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(SOLVENT NAPHTHA)
IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(SOLVENT NAPHTHA)
IATA : Environmentally hazardous substance, liquid, n.o.s.
(SOLVENT NAPHTHA)

14.3 Transport hazard class(es)

ADN : 9
ADR : 9
RID : 9
IMDG : 9
IATA : 9

AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294

This version replaces all previous versions.

14.4 Packing group

ADN

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Marine pollutant : yes

IATA (Cargo)

Marine pollutant : yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
: Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
E2	ENVIRONMENTAL HAZARDS	200 t	500 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2,500 t	25,000 t

Other regulations:

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2): Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance when it is used in the specified applications.

SECTION 16: Other information

Full text of H-Statements

H228	: Flammable solid.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H351	: Suspected of causing cancer.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Acute aquatic toxicity
Aquatic Chronic	: Chronic aquatic toxicity
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Irrit.	: Eye irritation
Flam. Sol.	: Flammable solids
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
91/322/EEC	: Europe. Commission Directive 91/322/EEC on establishing indicative limit values
CH SUVA	: Switzerland. Limit values at the work place

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AXIAL 50 EC

Version 11.0 Revision Date: 21.11.2017 SDS Number: S1450086294 This version replaces all previous versions.

91/322/EEC / TWA : Limit Value - eight hours
CH SUVA / TWA : Time Weighted Average
CH SUVA / STEL : Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Acute Tox. 4 H332
Skin Sens. 1 H317
Aquatic Chronic 2 H411

Classification procedure:

Based on product data or assessment
Based on product data or assessment
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CH / EN

AXIAL 50 EC

Version
11.0

Revision Date:
21.11.2017

SDS Number:
S1450086294

This version replaces all previous versions.
